






Drive Cage *Standard 3.5" devices 5.25" Drive Bay Solutions*

Following the traditional industrial system needs for stability, durability and toughness for storage drive operating condition, IEI provides various kinds of standard 3.5" devices 5.25" removable drive bay and modules for each different demands.

	SATA / IDE / SSD Solution		SATA / IDE / SSD	SATA Solution
				
Model Name	XWC-410030507220-RS	XWC-410030507230-RS	AS-25D2-R10	RD-03A-RS
Dimensions (L x W x H) (mm)	150 x 146 x 42	150 x 146 x 42	143 x 106 x 26	190 x 148 x 42
Material	Aluminum	Aluminum	Plastic body with stainless steel 2.5" HDD bracket	Aluminum alloy
Interface	SATA / IDE / SSD	SATA / IDE / SSD	SATA / IDE / SSD	SATA
Data Transfer Rate			No	up to 300MB/Sec
Drive Bay Space	One 5.25" Device Bay	One 5.25" Device Bay	Two 2.5" Device Bay	One 5.25" Device Bay
HDD Type	Internal 3.5" device bay	Internal 3.5" device bay	2.5" IDE / SATA SSD x 2	3.5" SATA
Cooling Fan			Open air design for maximum air flow and cooling	4010 ball bearing
Hot Swap	No	No	No	Yes
Keylock	No	No	No	Yes
Signal Out	No	No	No	Power on signal out (high) HDD access signal out (high)
Color	Black	White	Black	White / Black
G.W.	0.2kg	0.2kg	0.125kg	0.3kg

	SATA Solution			
				
Model Name	RHD-302SATA-RS	RHD-101SATA-R10	RHD-104SATA-R10	RHF-21-SATA-R10
Dimensions (L x W x H) (mm)	220 x 148 X 85.8	135 x 101.6 x 25.6	170 x 146 x 41.3	151.5 x 102 x 25.7
Material	Aluminum alloy	SECC	SECC	SECC
Interface	SATA	7-pin SATA x 2	7-pin SATA x 4	SATA
Data Transfer Rate	up to 300MB/Sec	Up to 600 MB/sec	Up to 600 MB/sec	No
Drive Bay Space	2 x 5.25" drive bay for 3 x 3.5" HDD	One 3.5" Device Bay	One 5.25" Device Bay	Internal 3.5" device bay
HDD Type	3.5" SATA	2.5" SAS or SATA I / II / III 1 x HDD/SSD	2.5" SAS or SATA I / II / III 4 x HDD/SSD	2.5" SATA HDD
Cooling Fan	8020 ball bearing (Removable)	Metal heat dispersion	2 x 40 mm rear outtake fan w/ aluminum heat dissipation	No
Hot Swap	Yes	Yes	Yes	Yes
Keylock	No	2 x segment key lock	No	Yes
Signal Out	3 x HDD power signal out (+5V, GND) 1 x Temperature overheat signal out (5V, GND) 1 x Fan fail signal out (5V, GND) 3 x HDD access signal out (+5V, GND) 1 x Reset signal out (High, GND)	1 x HDD power signal out 1 x HDD access signal out	4 x HDD power signal out 4 x HDD access signal out	1 x Female connector 1 x SATA LED signal connector 1 x Power LED connector 1 x Key on/off connector 1 x Power/SATA LED connector 1 x Male connector
Color	Black bezel and silver housing	Black	Black	Black
G.W.	1.0kg	0.483kg	0.95kg	0.3kg

1

Industrial
Computing
Solutions

2

Video
Capture
Solutions

3

Embedded
Computing
Solutions

4

Automation
Control

5

ORing
Network
Communication

6

Power Supply/
Peripherals

7

Panel
Solutions
Introduction