

ICP DAS CO., LTD.

No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County
30351, Taiwan, R.O.C.
www.icpdas.com



End of Life Notification

EOL notification date: 2024/6/12

Phased out model: I-7561

Last Order Date: While Supply Last

Dear Partners,

ICP DAS hereby formally announces the manufacturing discontinue and End of Life (EOL) of I-7561.

Within the effective warranty period, ICP DAS is committed to continue providing comprehensive after-sales service and technical support.

- Reason for termination: Phase out of USB Bridge chip
- Suggested replacement device: **I-7561U**
 - Status: Available
 - Please refer to the following table for cross reference information.

Model Name		I-7561	I-7561U
Product Status		While Supply Last	Available
USB	Specification	Fully Compliant with the USB 1.1/2.0/3.0	
	Bridge	Prolific Solution	FTDI Solution
	Driver	Windows 98/ME/2000/XP /Vista /7 /10 (64-bit)/Linux	Windows 98/ME/2000/XP/ Vista /7 /8 /10 /Linux
Serial Interface	RS-232	• TxD, RxD, GND	
	RS-422	• TxD+, TxD-, RxD+, RxD-	
	RS-485	• Data+, Data	
Baud Rate		300 ~ 115200 bps	300 ~ 921600 bps
Connector	USB	Type B	
	RS-232/422/485	Removable 10-Pin Terminal Block	
Cable Included		CA-USB18 (1.8 M Cable) x 1	
Dimensions (mm)		72 x 35 x 115 (W x L x D)	

For more information, please visit the link below:

<https://www.icpdas.com/en/product/I-7561U-G>