

i-8000 Compact PAC

SERIES

I-8000



Ordering Information:

I-8410: PAC
I-8410-G: I-8410 with Gary color



Ordering Information:

I-8411: PAC
I-8411-G: I-8411 with Gary color



Ordering Information:

I-8810: PAC
I-8810-G: I-8810 with Gary color



Ordering Information:

I-8811: PAC
I-8811-G: I-8811 with Gary color

Specifications & Features

- CPU 80188, 40MHz
- SRAM:
256K bytes (for I-8410/8810)
512K bytes (for I-8411/8811)
- Flash Memory:
256K bytes (for I-8410/8810)
512K bytes (for I-8411/8811)
- EEPROM: 2K bytes
- 64-bit hardware unique serial number (for I-8411/8811)
- Built-in Watchdog Timer
- Real Time Clock (for I-8411/8811)
- COM0: Internal use
- COM1: RS-232/Program download port
- COM2: RS-485
- COM3: RS-232/485
- COM4: RS-232 (I-8411/8811)
- S-MMI:
Small Man Machine Interface
- I/O Expansion Slot
4-slot for I-8410/8411
8-slot for I-8810/8811
- Power Supply: 20W
Unregulated +10Vdc to +30Vdc
- Power Consumption:
I-8410/I-8411: 3.9W
I-8810/I-8811: 5.1W
- Environment
Operating Temp.:
-25°C to + 75°C
Storage Temp.:
-30°C to + 85°C
- Humidity: 5 ~95%
- Dimensions:
354 x 110 x 75.5 mm (8-slot)
230 x 110 x 75.5 mm (4-slot)