







Dimension (W x D x H)	41 (W) x 114.9 (D) x 144.3 (H)mm
Weight (g)	675g
<b>Environmental</b>	
Storage Temperature	-40 to 85°C (-40 to 185°F)
Operating Temperature	-40 to 75°C (-40 to 167°F)
Operating Humidity	5% to 95% Non-condensing
<b>Regulatory approvals</b>	
EMC	CE EMC (EN 55024, EN 55032), EN50121-4 (compliant), FCC Part 15 B
EMI	EN 55032, CISPR32, EN 61000-3-2, EN 61000-3-3, FCC Part 15 B class A
EMS	EN 55024 (IEC/EN 61000-4-2 (ESD: Contact 4KV, Air 8KV), IEC/EN 61000-4-3 (RS: 3V), IEC/EN 61000-4-4 (EFT Power 0.5KV, Signal 0.5KV), IEC/EN 61000-4-5 (Surge: Power 0.5KV, RJ45 1KV), IEC/EN 61000-4-6 (CS: 3V), IEC/EN 61000-4-8(PFMF), IEC/EN 61000-4-11 (DIP)
Shock	IEC60068-2-27
Free Fall	IEC60068-2-31
Vibration	IEC60068-2-6
Safety	EN 60950-1 (LVD), UL61010-1,
MTBF	532,527 hours / Standard : Telcordia SR-332
Warranty	5 years

## Ordering Information

**IGPS-10A B-24V**



Code Definition	10/100/1000Base-T(X) P.S.E Port Number	Additional Port Number
<b>Option</b>	- <b>8</b> : 8 ports	- <b>0</b> : 0 port
Available Model	Model Name	Description
	IGPS-1080-24V	Industrial 8-port unmanaged Gigabit PoE Ethernet switch with 8x10/100/1000Base-T(X), 24VDC power input
<b>Packing List</b>		<b>Optional Accessories</b>
<ul style="list-style-type: none"> <li>IGPS-1080-24V x 1</li> <li>DIN-Rail Kit x 1</li> <li>Wall-mount Kit x 2</li> <li>Quick Installation Guide x 1</li> </ul>		<ul style="list-style-type: none"> <li>DR/SDR/DRP Series DIN-Rail power supply</li> </ul>