

# 63030-010180-000-RS


180 W 1U Type ATX  
Power Supply



## Specifications

Input Type	90~264 VAC Full Range				
Output Voltage	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb
	10 A (0.1 A min.)	14 A (0.2 A min.)	10 A (0.6 A min.)	0.3 A	2.5 A
Efficiency	85%				
Temperature	Operating: 0°C ~ 50°C, Storage: -20°C ~ 80°C				
MTBF (hrs)	100,000				
Output Connector	20+4-pin ATX, 4-pin 12V CPU, 1 x FDD, 1 x HDD, 2 x SATA				
Dimensions (mm)	150 x 81.5 x 40.5				

## Dimensions (Unit: mm)




## Ordering Information

Part No.	Description
63030-010180-000-RS	1U Flex ATX 180W Power Supply, 90~264VAC, ErP, CCL, RoHS

# 63030-010150-000-RS


150 W 1U Type ATX  
Power Supply



## Specifications

Input Type	90~264 VAC Full Range				
Output Voltage	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb
	10 A (0.1 A min.)	14 A (0.2 A min.)	10 A (0.6 A min.)	0.3 A	2.5 A
Efficiency	85%				
Temperature	Operating: 0°C ~ 50°C, Storage: -20°C ~ 80°C				
MTBF (hrs)	100,000				
Output Connector	20+4-pin ATX, 4-pin 12V CPU, 1 x FDD, 2 x HDD, 2 x SATA				
Dimensions (mm)	150 x 81.5 x 40.5				

## Dimensions (Unit: mm)



## Ordering Information

Part No.	Description
63030-010150-000-RS	1U Flex ATX 150W Power Supply, 90~264VAC, ErP, CCL, RoHS