



TABLE:

TC&C PART NO.	LENGTH "A"	LENGTH "B"
T1070E1361626-1	600±20mm	450REF
T1070E1361626-2	1000±30mm	850REF
T1070E1361626-3	470±20mm	250REF
T1070E1361626-4	500±20mm	250REF



ITEM	PART NUMBER	DESCRIPTION	QTY	REMARK
11	T911113300720XX	PVC LABEL 50*7MM,WHITE, MARKING"1-4"	4PCS	
10	T9410025013097	醋酸膠布,L:40*W:25MM	2PCS	
9	B993/8004	W=8.0MM PLASTIC BRAID 56*1*0.25*8 12 目 BLACK	A/R	
8	B440450161	OVER MALDING PVC, BLACK	A/R	
7	B44-72004C13501	INNER MOLDING HDPE, WHITE	A/R	
6	T504816013030Y5	SATA 7P FEMALE W/LOCK G/F CRIMP, BLACK	4PCS	
5	T50E10361310119	MINI SAS HD BODY COVER PLACTIC ABS 94V-0 BLACK 下殼(短)	1PC	
4	T50E10361210019	MINI SAS HD BODY COVER PLACTIC ABS 94V-0 BLACK 上殼	1PC	
3	T61E10000002XX	MINI SAS HD CONNECTOR KIT, WITH PCB,WHITE MARK C1-C9,D1-D9	1PC	
2	T61E10000001XX	MINI SAS HD CONNECTOR KIT, WITH PCB,WHITE MARK A1-A9,B1-B9	1PC	
1	T60-C16S1024-X	SAS 30#*2C+2DAHMM,100 OHM 1.0*2.32, 青 30#	A/R	

NOTE:
 1.OPEN/SHORT TEST:100%;
 2.CONDUCTOR RESISTANCE:5Ω;
 3.INSULATION RESISTANCE:20MΩ;
 4.HI-POT TEST:300V/DC;
 5.ALL MATERIALS MUST ACCORD WITH RoHS;

WIRING TABLE

TOLERANCE UNIT(mm)	APPROVALS	DATE	TC&C Electronic Co.,Ltd			
X. ±0.30	DRAWN Jen	08/02/2018	TITLE MINI SAS HD FOR CONTROLLER MINI SAS HD TO SATA 7P W/LOCK * 4 PORTS 180°, SAS 30AWG WITH PLASTIC BRAID			
X.X ±0.25	CHECKED Jenny	08/02/2018				
X.XXX ±0.15	APPROVED JOHNSON	08/02/2018				
X.XXX ±0.08			SCALE N.A.	PART NO. T1070E1361626-X	DRAWING NO. T1070E1361626-X-B	REV. B
ANGULAR ±2°			SHEET 1 OF 1	CUSTOMER PART NO.		