

	ErP/EuP Compliant
Environment	
Operating Temperature	0°C~60°C
Storage Temperature	-30°C~70°C
Humidity	5% ~95%, non-condensing

Ordering Information

NANO-ADL-P-i7C-R10	EPIC SBC supports Intel® Alder Lake-P Core™ i7-1255U processor with 8GB LPDDR4x memory on board default, with Dual HDMI,DP,IDPM,M.2 A key, M.2 B key, USB 3.2, SATA 6Gb/s, COM, IAUDIO,PCIe x4 for riser card and RoHS
NANO-ADL-P-i5C-R10	EPIC SBC supports Intel® Alder Lake-P Core™ i5-1235U processor with 8GB LPDDR4x memory on board default, with Dual HDMI,DP,IDPM,M.2 A key, M.2 B key, USB 3.2, SATA 6Gb/s, COM, IAUDIO,PCIe x4 for riser card and RoHS
NANO-ADL-P-i3C-R10	EPIC SBC supports Intel® Alder Lake-P Core™ i3-1215U processor with 8GB LPDDR4x memory on board default, with Dual HDMI,DP,IDPM,M.2 A key, M.2 B key, USB 3.2, SATA 6Gb/s, COM, IAUDIO,PCIe x4 for riser card and RoHS
NANO-ADL-P-CC-R10	EPIC SBC supports Intel® Alder Lake-P Celeron® 7305 processor with 8GB LPDDR4x memory on board default, with Dual HDMI,DP,IDPM,M.2 A key, M.2 B key, USB 3.2, SATA 6Gb/s, COM, IAUDIO,PCIe x4 for riser card and RoHS

Packing List

1 x NANO-ADL-P single board computer	1 x SATA cable
1 x QIG	