



USB to 1-Port RS-422, RS-485, RS-530 DB25 Serial Interface Adapter

Part: 2102 | **Model:** SeaLINK+485

The 2102 USB serial interface adapter provides a single USB to RS-422, RS-485, or RS-530 serial port for providing USB connectivity to legacy or non-USB compliant devices. SeaLINK® serial interface adapters support standard PC data rates up to 921.6K bps to provide you with the horsepower your serial I/O applications require.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. After installing the software, simply connect the SeaLINK serial interface adapter to your USB port and the device is immediately recognized by the system as a standard serial port.

Features & Specifications

USB to 1-Port RS-422, RS-485, RS-530 DB25 Serial Interface Adapter

Part: 2102 | Model: SeaLINK+485

Since 1986

Design & Manufacturing Experience

Long-term Availability Guaranteed

Lifetime Warranty

Features

- Compliant with RoHS and WEEE directives
- Configurable for RS-422, RS-485, or RS-530
- High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- Data rates to 921.6K bps
- Automatic RS-485 enable/disable
- All modem control signals implemented
- Hot-swappable
- Powered by USB connection
- DB-25M connector
- Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems
- Includes 6' USB device cable (Item# CA179)

Specifications

Family	SeaLINK
Communications Chip	USB/UART
Dimensions	3.8" (L) x 2.3" (W) x 1.0" (H)
Electrical Interface	RS-422, RS-485, RS-530
High Retention USB	Yes
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Max Data Distance	4000 feet
Max Data Rate	921.6K bps
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	1
Power Requirement	+5V @ 50mA
RoHS Compliant	Yes
Serial Connector(s)	DB25M
Storage Temperature	0°C to 70°C (32°F to 158°F)
USB Powered	Yes
USB Specification	1.1 Compliant, 2.0 Compatible