



Embedded USB to 1-Port RS-232, RS-422, RS-485 (Software Configurable) DB9 Serial Interface Adapter with PC Bracket

Part: 2128 | **Model:** SeaLINK/PC.SC

The SeaLINK® 2128 is a single port embedded USB to multi-interface serial adapter intended for mounting directly to a computer chassis, eliminating the need for an external converter and providing a clean, professional installation. All configuration and electrical interface selections are handled through the driver, so you never need to open the enclosure to set jumpers or switches. The serial port is software configurable for RS-232, RS-422, and RS-485 with the electrical interface settings maintained locally, allowing the host computer to be repaired or upgraded without reconfiguring the serial ports.

Sealevel SeaCOM USB software drivers and utilities make installation and operation easy using Microsoft Windows operating systems. After installing the software, simply connect the 2128 to an available USB header connector on your motherboard and the serial port is recognized as a standard COM port by the host system enabling compatibility with legacy software. All Sealevel SeaLINK USB serial adapters use a state-machine architecture that greatly reduces the host computer's overhead when communicating over multiple serial ports simultaneously while supporting data rates to 921.6K bps.

The 2128 includes a standard-sized PC bracket and ships with an internal USB cable (Item# CA260) that is compatible with many EBX and larger sized motherboards with 0.1 USB header connectors. For EPIC and smaller sized motherboards, an internal USB cable with a 2mm header connector (Item# CA383) is available as an option. Standard operating temperature range is 0°C to 70°C and extended temperature range (-40°C to 85°C) is optional.

Do you know that adapter design can impact your application? Find out how in this USB Serial performance report.

Features & Specifications

Embedded USB to 1-Port RS-232, RS-422, RS-485 (Software Configurable) DB9 Serial Interface Adapter with PC Bracket

Part: 2128 | Model: SeaLINK/PC.SC

Features

- Compliant with RoHS and WEEE directives
- Serial port software configurable for RS-232, RS-422, or RS-485
- High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- Supports data rates to 921.6K bps
- Automatic RS-485 enable/disable
- Powered by USB connection
- Single DB9M connector with full modem control signals implemented in RS-232 mode
- Sealevel SeaCOM software supports Windows 7 and newer operating systems
- Includes 14 internal USB header cable (Item# CA260)

Specifications

Family	SeaLINK
Operating Temperature	0°C to 70°C (32°F to 158°F)
Dimensions	2.9 (L) x 2.4 (W)
Electrical Interface	RS-232, RS-422, RS-485
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Max Data Distance	50 feet (RS-232) 4000 feet (RS-485)
Max Data Rate	921.6K bps
Communications Chip	USB/UART
# of Ports	1
PC Bracket	Standard Height
Power Requirement	+5V @ 200mA
RoHS Compliant	Yes
Serial Connector(s)	DB9M
Software Configurable	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Powered	Yes
USB Specification	1.1 Compliant 2.0 Compatible