

Features & Specifications

Ethernet Modbus TCP to 32 Isolated Inputs

Part: 430E | **Model:** Seal/O-430E

Features

- 10/100BaseT Ethernet Modbus TCP interface
- 32 optically isolated inputs
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- DIN rail mount or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

Specifications

| | |
|---------------------------------|--|
| Family | Seal/O |
| Digital I/O | Isolated Inputs |
| Dimensions | 7.5 (L) x 5.1 (W) x 1.3 (H) |
| Extended Temperature | Call for Options |
| Humidity Range | 10 – 90% Relative Humidity, Non-Condensing |
| Input Isolation | 300V |
| Input Range | 5-30 VDC |
| Input Impedance | 6.2K Ohms (in series) |
| Host Interface(s) | Ethernet |
| Number of Inputs/Outputs | 32 Inputs |
| Operating Temperature | 0°C to 70°C (32°F to 158°F) |
| # of Ports | 32 |
| Power Requirement | 9-30 VDC @ 1.9W |
| RoHS Compliant | Yes |
| Storage Temperature | -50°C to 105°C (-58°F to 221°F) |