



USB to 32 Optically Isolated Inputs

Part: 430U | **Model:** Seal/O-430U

Interface 32 optically isolated inputs via any USB connection with the Seal/O-430U. Inputs can range from 5-30VDC and provide 300V external isolation. Connection is made using convenient 3.5mm removable screw terminal connectors. To facilitate easy wiring, the inputs are grouped in 4-bit segments that each share a common. The Seal/O-430U is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-430U using industry-standard Modbus RTU protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

The Seal/O-430U integrates Sealevel's SeaLATCH locking USB port, which is fully compatible with standard USB cables. When used with the included USB cable with a SeaLATCH USB type B connector, the metal thumbscrew provides a secure connection to the device and prevents accidental cable disconnection.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

Features & Specifications

USB to 32 Optically Isolated Inputs

Part: 430U | Model: Seal/O-430U

Features

- 32 optically isolated inputs
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- Sealevel's SeaLATCH locking USB port provides secure connection with SeaLATCH USB cables via metal thumbscrews
- DIN rail mount or table mount
- Includes 6' USB type A to SeaLATCH USB type B device cable (Item# CA356)
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

Specifications

Family	Seal/O
Digital I/O	Isolated Inputs
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Input Isolation	300V
Input Range	5-30 VDC
Input Impedance	6.2K Ohms (in series)
Host Interface(s)	USB
Number of Inputs/Outputs	32 Inputs
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	32
Power Requirement	9-30 VDC @ 0.6W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Specification	1.1 Compliant 2.0 Compatible