



USB to 96 Channel TTL Digital Interface Kit - 462U + (2) CA237 Cables

Part: 462U-KT | **Model:** Seal/O-462U with Cables

Control and monitor up to 96 channels of buffered drive digital I/O via any USB connection with the Seal/O-462U. The interface module addresses the 96 channels of I/O as 12 eight-bit ports, each programmable as input or output. Using the included shielded cables (Item# CA237), connect up to four industry-standard relay racks for PC based control and automation of equipment including sensors, switches, security control systems, and other industrial automation systems. The Seal/O-462U is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-462U using industry-standard Modbus RTU protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

The Seal/O-462U-KT integrates Sealevel's SeaLATCH locking USB port, which is fully compatible with standard USB cables. When used with the included USB cable with a SeaLATCH USB type B connector, the metal thumbscrew provides a secure connection to the device and prevents accidental cable disconnection.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

Features & Specifications

USB to 96 Channel TTL Digital Interface Kit - 462U + (2) CA237 Cables

Part: 462U-KT | **Model:** Seal/O-462U with Cables

Features

- 96 channels of buffered TTL I/O
- Each 8-bit port individually configurable as input or output
- Includes two 6' cables, part number CA237, each with a DB-78 Male connector to dual 50-pin ribbon connectors
- Easily connects to industry-standard solid-state relay racks with 50-pin connectors
- Status indicator LEDs for Communication, Fault, and Power
- Input power via terminal block or modular connector
- Sealevel's SeaLATCH locking USB port provides secure connection with SeaLATCH USB cables via metal thumbscrews
- DIN rail or table mount
- Includes 6' USB type A to SeaLATCH USB type B device cable (Item# CA356)
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

Specifications

Family	Seal/O
Digital I/O	TTL I/O
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Kit	Yes
Number of Inputs/Outputs	96 TTL
Operating Temperature	0°C to 70°C (32°F to 158°F)
Output Power	+5V @ 1A (5W) max.
Output Specification	Sink up to 64mA, Source up to 32mA
# of Ports	96
Power Requirement	9-30 VDC @ 2.0W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Specification	1.1 Compliant, 2.0 Compatible