



RS-232 Modbus RTU to 32 Open-Collector Outputs

Part: 540S | **Model:** Seal/O-540S

The Seal/O-540S is a RS-232 Modbus RTU interface to 32 open-collector outputs. The open-collector outputs provide high current sinking over a large operating voltage. Each open-collector output circuit includes a flyback diode for protection when interfacing highly inductive loads, such as DC motors. Outputs are grouped in eight-bit ports which share high and low voltage contacts via 3.5mm terminal blocks.

The Seal/O-540S is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-540S using the Sealevel SeaMAX API software libraries or use any Modbus RTU compliant device. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

Features & Specifications

RS-232 Modbus RTU to 32 Open-Collector Outputs

Part: 540S | Model: Seal/O-540S

Features

- RS-232 Modbus RTU interface
- 32 open collector outputs
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- Optional DIN rail or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

Specifications

Family	Seal/O
Digital I/O	Open-Collector Outputs
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	RS-232
Number of Inputs/Outputs	32 Outputs
Operating Temperature	-25°C to 85°C (-13°F to 185°F)
Output Dissipation	Max. 1000mA (single), Max. 2000mA (port)
Output Isolation	2500VAC RMS, 3500VDC
Output Power	DC 60W max.
Output Type	Open-Collector
Output Voltage	Max. 60VDC
# of Ports	32
Power Requirement	9-30 VDC @ 2.1W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)