



Control 32 open-collector outputs via a wireless network with the Seal/O-540W. The open-collector outputs provide high current sinking over a large operating voltage. Each open-collector output circuit includes a flyback diode for protection when interfacing highly inductive loads, such as DC motors. Outputs are grouped in eight-bit ports which share high and low voltage contacts via 3.5mm terminal blocks.

Communicate with the Seal/O-540W over Wi-Fi (802.11b and 802.11g) networks using industry-standard Modbus TCP protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. Security features include WEP and the latest WPA-TKIP and WPA2-AES encryption standards.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

ICP Deutschland GmbH | +49(0)7121-14323-20 | [sales@icp-deutschland.de](mailto:sales@icp-deutschland.de) | [www.icp-deutschland.de](http://www.icp-deutschland.de)

Features & Specifications

Wi-Fi 802.11b/g Modbus TCP to 32 Open-Collector Outputs

Part: 540W | Model: Seal/O-540W

Features

- Complies with 802.11g and 802.11b (2.4GHz) networking standards
- Wireless security supports WEP, WPA-TKIP, and WPA2-AES encryption standards
- 32 open collector outputs
- Removable screw terminals simplify field wiring
- Status indicator LEDs for Communication, Fault, and Power
- Input power via terminal block or modular connector
- Optional DIN rail or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

Specifications

Family	Seal/O
Digital I/O	Open-Collector Outputs
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	Wi-Fi (802.11bgn)
Number of Inputs/Outputs	32 Outputs
Operating Temperature	-25°C to 85°C (-13°F to 185°F)
Output Dissipation	Max. 1000mA (single), Max. 2000mA (port)
Output Isolation	2500VAC RMS, 3500VDC
Output Power	DC 60W max.
Output Type	Open-Collector
Output Voltage	Max. 60VDC
# of Ports	32
Power Requirement	9-30 VDC @ 3.9W
Storage Temperature	-50°C to 105°C (-58°F to 221°F)