



PCI 2-Port RS-232 Serial Interface

Part: 7202 | **Model:** COMM+232.PCI

The 7202 PCI serial interface provides two RS-232 serial ports capable of data rates to 460.8K bps. Each RS-232 port implements all modem control signals for maximum compatibility with a wide range of peripherals. The 7202 utilizes 16C850 UARTs that provide 128-byte Tx/Rx FIFOs.

Sealevel's SeaCOM software makes installation and operation easy using Microsoft Windows and Linux operating systems.

Features & Specifications

PCI 2-Port RS-232 Serial Interface

Part: 7202 | **Model:** COMM+232.PCI

Features

- 16C850 buffered UARTs with 128-byte FIFOs
- Data rates to 460.8K bps
- All modem control signals implemented
- Two DB-9M connectors

Specifications

Communications Chip	16C850
Electrical Interface	RS-232
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	PCI
Max Data Distance	50 feet
Max Data Rate	460.8K bps
Operating Temperature	0°C to 70°C (32°F to 158°F)
PC Bracket	Standard Height
# of Ports	2
Serial Connector(s)	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
UART Series	850 UART