

Low Profile PCI 1-Port RS-232, RS-422, RS-485, RS-530, RS-530A, V.35 Synchronous Serial Interface (uses Z16C32)

Part: 5104 | Model: ACB-Ultra.LPCI

The 5104 Low Profile PCI serial interface provides one synchronous serial port configurable for RS-232, RS-422, RS-485, RS-530, RS-530A, or V.35. The board is capable of data rates to 10M bps. The 5104 utilizes a Z16C32 Integrated Universal Serial Controller (IUSC) with built-in DMA controller and 32-byte FIFO buffer. The board is MD1 Low Profile and Universal Bus (3.3V and 5V) compatible.

The 5104 is compatible with any low profile PCI slot. If you have a standard size PCI slot, be sure to select the standard profile bracket.

Software support, critical for successful synchronous communication development, is provided through Sealevel's SeaMAC synchronous serial driver. HDLC/SDLC protocols are supported as well as certain configurations of Monosync, Bi-sync and Raw modes.

Features & Specifications

Low Profile PCI 1-Port RS-232, RS-422, RS-485, RS-530, RS-530A, V.35 Synchronous Serial Interface

Part: 5104 | Model: ACB-Ultra.LPCI

Features

- · Compliant with RoHS and WEEE directives
- Configurable for RS-232, RS-422, RS-485, RS-530, RS-530A, or V.35
- Z16C32 Integrated Universal Serial Controller (IUSC) with built-in DMA controller and 32-byte FIFO buffer
- 256K bytes of onboard RAM/link list DMA supported
- · Data rates to 10M bps
- MD1 Low Profile and Universal Bus (3.3V and 5V) compatible
- Requires 3.3V power on PCI bus
- · DB-25M connector

Specifications

Communications ControllerZ16C32 IUSCCommunications ControllerZ16C32Electrical InterfaceRS-232, RS-422, RS-485, RS-530, RS-530AHumidity Range10 - 90% Relative Humidity, Non-CondensingHost Interface(s)PCIMax Data Distance50 feet (RS-232)4000 feet (RS-485)Max Data Rate10M bps (burst)Operating Temperature0°C to 70°C (32°F to 158°F)PC BracketLow Profile		
Controller Electrical Interface RS-232, RS-422, RS-485, RS-530, RS-530A Humidity Range 10 - 90% Relative Humidity, Non-Condensing PCI Max Data Distance 50 feet (RS-232)4000 feet (RS-485) Max Data Rate 10M bps (burst) Operating Temperature 0°C to 70°C (32°F to 158°F)	Communications Chip	Z16C32 IUSC
Humidity Range 10 - 90% Relative Humidity, Non-Condensing Host Interface(s) PCI Max Data Distance 50 feet (RS-232)4000 feet (RS-485) Max Data Rate 10M bps (burst) Operating Temperature 0°C to 70°C (32°F to 158°F)		Z16C32
Humidity Range Non-Condensing Host Interface(s) PCI Max Data Distance 50 feet (RS-232)4000 feet (RS-485) Max Data Rate 10M bps (burst) Operating Temperature 0°C to 70°C (32°F to 158°F)	Electrical Interface	
Max Data Distance 50 feet (RS-232)4000 feet (RS-485) Max Data Rate 10M bps (burst) Operating Temperature 0°C to 70°C (32°F to 158°F)	Humidity Range	
Max Data Rate 10M bps (burst) Operating Temperature 0°C to 70°C (32°F to 158°F)	Host Interface(s)	PCI
Operating Temperature 0°C to 70°C (32°F to 158°F)	Max Data Distance	50 feet (RS-232)4000 feet (RS-485)
	Max Data Rate	10M bps (burst)
PC Bracket Low Profile	Operating Temperature	0°C to 70°C (32°F to 158°F)
	PC Bracket	Low Profile
# of Ports 1	# of Ports	1
RoHS Compliant Yes	RoHS Compliant	Yes
RS-485 Operation Full Duplex (4 wire)Half Duplex (2 wire	RS-485 Operation	Full Duplex (4 wire)Half Duplex (2 wire)
Serial Connector(s) DB25M	Serial Connector(s)	DB25M
Storage Temperature -50°C to 105°C (-58°F to 221°F)	Storage Temperature	-50°C to 105°C (-58°F to 221°F)
V.35 Yes	V.35	Yes