V1.1 July, 2023



IGS-9080-LA-PN

Industrial Slim 8-port managed Gigabit Ethernet switch with 8x10/100/1000Base-T(X) ports, PROFINET Version

Features

- Support O-Ring (recovery time < 30ms) and MSTP(RSTP/STP compatible) for Ethernet Redundancy
- O-Chain allow multiple redundant network rings
- Support standard IEC 62439-2 MRP*NOTE (Media Redundancy Protocol) function
- Support IPV6 new internet protocol version
- Support Modbus TCP protocol
- Provided HTTPS/SSH protocol to enhance network security
- Support SMTP client and NTP server protocol
- Support IP-based bandwidth management
- Support application-based QoS management
- Support Device Binding security function
- Support DOS/DDOS auto prevention
- Support auto-negotiation and auto-MDI/MDIX
- Support full and half duplex mode
- IGMP v2/v3 (IGMP snooping support) for filtering multicast traffic
- Support SNMP v1/v2c/v3 & RMON & 802.1Q VLAN Network Management
- Support ACL, TACACS+ and 802.1x User Authentication for security
- Support 9.6K Bytes Jumbo Frame
- Syslog/SNMP Trap notification for warning of unexpected event
- Support **DBU-01** backup unit device to quickly backup/restore configuration
- Web-based ,SNMP v1/v2c/v3, Telnet, Console (CLI), and Windows utility (Open-Vision) configuration
- Support LLDP Protocol
- Rigid IP-30 housing design
- DIN-Rail and wall mounting enabled













*NOTE: This function is available by request only


Introduction

IGS-9080-LA-PN is layer2 managed Ethernet switch with 8x10/100/1000Base-T(X) ports, which is designed for various industrial applications, including manufacturing, process automation, transportation, and energy industries. The PROFINET certification of this product line ensures its compliance with rigorous industry standards and seamless communication compatibility with PROFINET systems.

The switch support Ethernet Redundancy protocol, O-Ring (recovery time < 30ms) and MSTP (RSTP/STP compatible) can protect your mission-critical applications from network interruptions or temporary malfunctions with its fast recovery technology. And support wide operating temperature from -40 °C to 75 °C. IGS-9080-LA-PN can also be managed centralized and convenient by Open-Vision, except the Web-based interface, Telnet and console (CLI) configuration.


- O-Ring: O-Ring is ORing's proprietary redundant ring technology, with recovery time of less 30 milliseconds and up to 250 nodes. The O-Ring redundant ring technology can protect mission-critical application from network interruptions or temporary malfunction with its fast recover technology.
- <u>O-Chain</u>: O-Chain is the revolutionary network redundancy technology that provides the add-on network redundancy topology for any backbone network, O-Chain allows multiple redundant network rings of different redundancy protocols to join and function together as a larger and more robust compound network topology. O-Chain providing ease-of-use while maximizing fault-recovery swiftness, flexibility, compatibility, and cost-effectiveness in one set of network redundancy topology.
- MRP*NOTE: Media Redundancy Protocol (MRP) is a data network protocol standardized by the IEC 62439-2. It allows rings of Ethernet switches to overcome any single failure with recovery time much faster than achievable with Spanning Tree Protocol.
- **IP-based Bandwidth Management :** The switch provide advanced IP-based bandwidth management which can limit the maximum bandwidth for each IP device. User can configure IP camera and NVR with more bandwidth and limit other device bandwidth.
- Application-Based QoS: The switch also support application-based QoS. Application-based QoS can set highest priority for data stream according to TCP/UDP port number.
- <u>Device Binding Function</u>: ORing special Device Binding function can only permit allowed IP address with MAC address to access the network. Hacker cannot access the IP surveillance network without permission. It can avoid hacker from stealing video privacy data and attacking IP camera, NVR and controllers.
- Advanced DOS/DDOS Auto Prevention: The switch also provided advanced DOS/DDOS auto prevention. If there is any IP flow become big in short time, the switch will lock the source IP address for certain time to prevent the attack. It's hardware based prevention so it can prevent DOS/DDOS attack immediately and completely.
- Modbus TCP: This is a Modbus variant used for communications over TCP/IP networks.


*NOTE: This function is available by request only




Open-Vision


ORing's switches are intelligent switches. Different from other traditional redundant switches, ORing provides a set of Windows utility (Open-Vision) for user to manage and monitor all of industrial Ethernet switches on the industrial network.







Dimension




Specifications

ORing Switch Model	IGS-9080-LA
Physical Ports	
10/100/1000Base-T(X) with Ports in	_
RJ45 Auto MDI/MDIX	8
Technology	
	IEEE 802.3 for 10Base-T
	IEEE 802.3u for 100Base-TX
Ethernet Standards	IEEE 802.3ab for 1000Base-T
	IEEE 802.3x for Flow control
	IEEE 802.3ad for LACP (Link Aggregation Control Protocol)
	IEEE 802.1p for COS (Class of Service)
	IEEE 802.1Q for VLAN Tagging
	IEEE 802.1Q-2014 MSTP (compatible with STP/RSTP)
	IEEE 802.1x for Authentication
	IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)
MAC Table	8k
Priority Queues	8
Processing	Store-and-Forward
Share Data Buffer	4Mbit
Switch Properties	Switching latency: 7 us
	Switching bandwidth: 8Gbps Throughout (neglect per accord) : 11 OMpps@64Butes perlet
	Throughput (packet per second): 11.9Mpps@64Bytes packet Max. Number of Available VLANs: 4095
	VLAN ID Range: VID 1 to 4094
	IGMP multicast groups: 256 for each VLAN
	Port rate limiting: User Define
Jumbo frame	Up to 9.6K Bytes
545646	Device Binding security feature
	Enable/disable ports, MAC based port security
	Port based network access control (802.1x)
Security Features	VLAN (802.1Q) to segregate and secure network traffic
	Radius centralized password management
	SNMPv3 encrypted authentication and access security
	Https / SSH enhance network security
	MSTP (RSTP/STP compatible)
	Redundant Ring (O-Ring) with recovery time less than 30ms over 250 units
	TOS/Diffserv supported
	Quality of Service (802.1p) for real-time traffic
Software Features	VLAN (802.1Q) with VLAN tagging
	IGMP Snooping IP-based bandwidth management
	Application-based QoS management
	DOS/DDOS auto prevention
	Port configuration, status, statistics, monitoring, security
	DHCP Server/Client/Relay
	SMTP Client
	Modbus TCP
	NTP server
Network Redundancy	O-Ring
	O-Chain
	MRP*NOTE
	MSTP (RSTP/STP compatible)
PROFINET conformance class	Conformance-class B
RS-232 Serial Console Port	RS-232 in RJ45 connector with console cable. 115200bps, 8, N, 1
LED Indicators	
Power Indicator (PWR)	Green: Power LED x 3
Ring Master Indicator (R.M.)	Green: Indicates that the system is operating in O-Ring Master mode
O Binn India (/ C)	Green: Indicates that the system operating in O-Ring mode
O-Ring Indicator (Ring)	Green Blinking: Indicates that the Ring is broken.
Fault Indicator (Fault)	Amber: Indicate unexpected event occurred

10/100/1000Base-T(X) RJ45 Port Indicator	Upper for Link/Act indicator, Green for Port LINK/ACT indicator Lower for speed indicator: Green for 1000Mbps / Amber for 100Mbps / off-light for 10Mbps
Fault Contact	
Relay	Relay output to carry capacity of 1A at 24VDC
Reset Function	
Reset Button	< 5 sec: System reboot, > 5 sec: Factory default
Power	
Redundant Input power	Dual 12 to 48VDC on 6-pin terminal block
Power consumption (Typ.)	13.2 Watts
Overload current protection	Present
Reverse Polarity Protection	Present
Physical Characteristic	
Enclosure	IP-30 Metal
Dimension (W x D x H)	54.3 (W) x 120 (D) x 145.1 (H) mm (2.13 x 4.72 x 5.71 inches)
Weight	779g
Environmental	
Storage Temperature	-40 to 85°C (-40 to 185°F)
Operating Temperature	-40 to 75°C (-40 to 167°F)
Operating Humidity	5% to 95% Non-condensing
Regulatory Approvals	
EMC	CE EMC (EN 55035, EN 55032), FCC Part 15 B
EMI	EN 55032, CISPR32, EN 61000-3-2, EN 61000-3-3, FCC Part 15 B class A
EMS	IEC/EN 61000-4-2 (ESD) IEC/EN 61000-4-3 (RS) IEC/EN 61000-4-4 (EFT) IEC/EN 61000-4-5 (Surge) IEC/EN 61000-4-6 (CS), IEC/EN 61000-4-8(PFMF),
Shock	IEC60068-2-27
Free Fall	IEC60068-2-31
Vibration	IEC60068-2-6
Safety	UL61010-1
Warranty	5 years

*NOTE: This function is available by request only

Ordering Information



Packing List

- IGS-9080-LA-PN x 1
 DIN-Rail Kit x 1
- ORing Tool CD x 1
- Quick Installation Guide x 1
- Wall-mount Kit x 2
- Console Cable x 1

Optional Accessories

Open-Vision M500 : Powerful Network

Management Windows Utility Suit, 500 IP devices

DR/SDR/NDR series : DIN-Rail power supply

DBU-01 : backup unit device