RM24200

2U High Flexibility Industrial Server Chassis

Features & Benefits

- Depth 18" of chassis for space-sensitive applications
- Optimized fan placement for better cooling performance
- Cushion on drive cages to depress HDD& ODD vibration
- Removable drive cages for easy installation
- Supports PS/2 PSU and other standard components to lower TCO

88.1 mm / 3.5"

430 mm / 16.9"

457.2 mm / 18"

2-Door Front Bezel

Aluminum Bezel Frame

Specification

M/B Form Factor	• Micro ATX (9.6" x 9.6")
Dimension (D x W x H)	• 457.2 x 430 x 88 (mm) , 18" x 16.9" x 3.5"
Drive Bay	• Exposed: 2 x 5.25" + 1 x 3.5" + 1 x slim ODD • Internal: 2 x 2.5"
PSU Form Factor	• PS/2 Single (rear)
Indicators	• 1 x Power Status, 1 x HDD Activity, 2 x LAN Activity
Front Control	• Power On/Off, System Reset, 2 x USB2.0/ USB3.0 (Option)
Cooling Fans	• Front: 1 x 80mm (T=32mm), Rear: 2 x 40mm (T=28mm) (Option)
System Security	• Intrusion switch (Option)
Slot Opening	• 4 x low profile
Metal Thickness	• 1.0mm
Materials	• SGCC
HDD Backplane	• N/A
Net Weight	• 6.9 kg
Gross Weight	• 9.3 kg
Cubic Feet	• 2.5
Container Info.*	• 20': 388, 40': 788, 40'H: 940

*Single Packing

Optional Items

	Order Code	Description
Cable	26H11324102A0	PSU extension cable, 24P to 24P ,250mm
	26H11324103A0	PSU extension cable, 8P to 4P+4P,400mm
	84H324110-010	Intrusion switch, 2-pin, 500mm
Drive Cage	84H324110-008	1 x 5.25" &1 x 3.5" drive bays
	84H324110-007	1 x 5.25" & 1 x slim ODD bays
Slide Rail	84H341300-002	22", for 2U/3U/4U

※PSU ※ M/B Support ※ I/O Gasket ※ Air Duct ※ (Detailed in CHENBRO websites)

1 x 5.25" + 1 x 3.5"
Removable drive bay

1 x 5.25" + 1 x slim ODD
Removable drive bay

Anti-vibration drive cage

2.5" cage with
80mm fan

Order Information

Order Code	M/B	Bezel	Cooling Fan(mm)	PCI Slot	PSU	Slide Rail
RM24200-L	9.6" x 9.6"	Al. Frame	1 x 8032	4 x LP	Option	Option
RM24200-L2	9.6" x 9.6"	2-door	1 x 8032	4 x LP	Option	Option