



eDP	1 x eDP Header (Optional)
Backlight	1 x Backlight Header
Fan	1 x 4 Pin CPU Fan Header
SATA	2 x SATA III Connector – 1 SATA port Multiplexed with M.2 B key SATA.
SATA Power	1 x 4 pin SATA Power Connector (3.3V, 5V, 12V) 1 x 3 pin SATA Power Connector (5V)
Speaker Header	1 x speaker header Header with amplifier
Audio Header	1 x Audio Header (Mic-in and Line-out)
Front Panel	1 x Front Panel Header
Buzzer	1 x Onboard Buzzer
CMOS Battery	1 x Cable Type Battery
DC-In	1 x 4 Pin DC-In Connector
<b>Rear I/O</b>	
DisplayPort	1 x DisplayPort1.4a 1 x HDMI1.4
LAN	2 x RJ-45 Connectors
USB	3 x USB 3.2 Gen2 Type A 1 x USB 3.2 Gen2 Type C (PD15W, 5V/3A, DP alt, USB3.2 Gen2)
Remote power on/off	2-pin remote power on/off header (terminal block type)
<b>Power &amp; Connector</b>	8V~26V (tolerance 7.2~28.8V) DC-In (Mini-fit type)
<b>Regulatory Compliance</b>	CE, FCC
<b>Operation Environment</b>	
Temperature	-25~60°C
Humidity	10% to 95% non-condensing
<b>Storage Environment</b>	
Temperature	-40 C to 85 C
Humidity	10% to 95% non-condensing
<b>Supported OS</b>	Microsoft Windows 10/Windows 11 64-bit, Linux Ubuntu 22.04